

PATENT ABSTRACTS OF JAPAN

(11) Publication number :

09-045893

(43) Date of publication of application : 14.02.1997

(51) Int.CI.

H01L 29/762

H01L 21/339

G01K 1/14

G01K 7/01

G02B 7/28

G03B 13/36

H01L 27/148

H04N 5/335

(21)Application number : 07-194418 (71)Applicant : SONY CORP

(22)Date of filing : 31.07.1995 (72)Inventor : MAKI YASUTO
NARABE TADAKUNI

(54) TEMPERATURE DETECTOR, CHARGE TRANSFER DEVICE MOUNTING IT, AND CAMERA

(57) Abstract:

PROBLEM TO BE SOLVED: To realize an on-chip temperature detector so as to precisely detect the temperature of a device to measure by a method wherein the temperature of a device is detected taking advantage of a dark current induced in a charge transfer section.

SOLUTION: In a reset pulse generating circuit 16, reset pulses ϕ_{rs} are generated before signal charge is transferred while signal is steadily outputted, and on the other hand, reset pulses ϕ_{rs} are generated as much thinned out while temperature detection is carried out. Therefore, the dark current charge of charge transfer registers 14 is transferred, collected at a floating, diffusion, and added together, so that a large dark current

can be obtained. The output voltage of a charge voltage converter 17 is led out as a signal voltage while signal charge is transferred, and the output voltage of a charge voltage converter 17 is led out as a temperature detection voltage while no signal charge is transferred. By this setup, an on-chip temperature detector can be realized, so that the temperature of a device to measure can be accurately detected.

